

AD-A258 490



DOCUMENTATION PAGE

Form Approved
OMB No. 0704-0188

1a. REPORT SECURITY CLASSIFICATION Unclassified			1b. RESTRICTIVE MARKINGS	
2a. SECURITY CLASSIFICATION AUTHORITY			3. DISTRIBUTION / AVAILABILITY OF REPORT Unlimited	
2b. DECLASSIFICATION / DOWNGRADING SCHEDULE				
4. PERFORMING ORGANIZATION REPORT NUMBER(S) DOD POP HMTR/AYD 92-014			5. MONITORING ORGANIZATION REPORT NUMBER(S)	
6a. NAME OF PERFORMING ORGANIZATION Packaging Division, AED	6b. OFFICE SYMBOL (If applicable) SMCAR-AEP	7a. NAME OF MONITORING ORGANIZATION		
6c. ADDRESS (City, State, and ZIP Code) U.S. Army, ARDEC Picatinny Arsenal, NJ 07806-5000		7b. ADDRESS (City, State, and ZIP Code)		
8a. NAME OF FUNDING / SPONSORING ORGANIZATION	8b. OFFICE SYMBOL (If applicable)	9. PROCUREMENT # 92-31306 		
8c. ADDRESS (City, State, and ZIP Code)		10. SOURCE OF FUNDING NUMBERS		
		PROGRAM ELEMENT NO.	PROJECT NO.	TASK NO.
		WORK UNIT ACCESSION NO.		
11. TITLE (Include Security Classification) Performance Oriented Packaging Report for M7 Non-Electric Blasting Cap				
12. PERSONAL AUTHOR(S) Sniezek, Frank				
13a. TYPE OF REPORT Final	13b. TIME COVERED FROM _____ TO _____	14. DATE OF REPORT (Year, Month, Day) 92-11-02		15. PAGE COUNT
16. SUPPLEMENTARY NOTATION				
17. COSATI CODES			18. SUBJECT TERMS (Continue on reverse if necessary and identify by block number)	
FIELD	GROUP	SUB-GROUP	Performance Oriented Packaging, POP, M7 Non-Electric Blasting Cap, Mil-B-2427 woodbox	
19. ABSTRACT (Continue on reverse if necessary and identify by block number)				
This POP report is for the M7 Non-Electric Blasting Cap which is packaged 480/Mil-B-2427 wood box. This report describes the results of testing conducted.				
<div data-bbox="115 1617 561 1787" data-label="Text"> <p>DISTRIBUTION STATEMENT A Approved for public release Distribution Unlimited</p> </div> <div data-bbox="1123 1532 1486 1766" data-label="Text"> <p>DTIC SELECTE DEC 14 1992 S B D</p> </div>				
20. DISTRIBUTION / AVAILABILITY OF ABSTRACT <input type="checkbox"/> UNCLASSIFIED/UNLIMITED <input type="checkbox"/> SAME AS RPT <input type="checkbox"/> DTIC USERS			21. ABSTRACT SECURITY CLASSIFICATION UNCLASSIFIED	
22a. NAME OF RESPONSIBLE INDIVIDUAL STEVE RUFFINI			22b. TELEPHONE (Include Area Code) (201) 724-2515	22c. OFFICE SYMBOL SMCAR-AEP

92 12 11 032

I. REPORT NUMBER: DOD POP HMTR/AYD 92-014

II. TITLE: Performance Oriented Packaging Report for Cap, Blasting,
Non-Electric: M7

PERFORMING ACTIVITY: ARDEC

ADDRESS: Department of the Army
ARDEC, SMCAR-AEP
HQ, U.S. Army Armament, Munitions, and Chemical Command
Picatinny Arsenal, NJ 07806-5000

DATE: 2 Nov 92

Approved for public release; Distribution is unlimited

EXCLUDED FROM AUTOMATIC DOWNGRADING AND DECLASSIFICATION

Accession For	
NTIS GRA&I	<input checked="checked" type="checkbox"/>
DTIC TAB	<input type="checkbox"/>
Unannounced	<input type="checkbox"/>
Justification	
By	
Distribution/	
Availability Codes	
Dist.	Avail and/or Special
A-1	

1. DATA SHEET

CONTAINER

Type: Box
UN Code: 4C1
Nomenclature: Box, Ammunition, Packing: Wood, Nailed
Specification Number: Type II, Class 2, Grade A, Mil-B-2427
Drawing Number: N/A
Material: Wood
Gross Weight: 70
Outside Dimensions: 12 5/8 x 15 x 12 1/4
Inside Dimensions: 9 1/2 x 13 1/4 x 9 3/4

PRODUCT

Name: Cap, Blasting, Non-Electric: M7
Drawing Number: 8830948
Specification Number: Mil-C-45469
United Nations Number: 0029
Physical State: Solid
Amount per Container: 480

2. BACKGROUND, TESTS, AND RESULTS

Reference the following document:

- a. 49CFR, October 1, 1991 Edition

Instead of testing with the actual item, three wooden boxes built to the same specification but packed with a fiberboard box loaded with sand to a gross weight of 70 pounds were tested.

A Stacking Test was conducted on one container with a weight of 910 pounds for 72 hours in lieu of three containers for 24 hours. This weight exceeds the minimum requirement for a 10 foot stack height which is 686 pounds.

A Loose Cargo Test was conducted on three containers for one hour. The packages were tested at a vibration table frequency such that the bottom of the packages were raised 1/4 inch from the platform, which exceeds the requirement of 1/16 inch.

A Four Foot Drop Test was conducted on one of the containers that was subjected to the Loose Cargo Test. One container was dropped five times at different orientations as follows: top, bottom, long side, short side, and a top corner at the closure. This exceeds the requirement of one drop per container.

Test results indicated no leakage or spillage of the contents from the containers following any of the tests conducted, meeting the requirements of the 49 CFR.